



## Hollow Wall Anchors

### Product Description

The Hollow Wall Anchor is an anchor made entirely of steel. It is vibration resistant and comes with three different head styles. For a faster result and an easier way to install, try the self-drilling Wallgripper from Cobra.

### Features & Benefits

- ▶ Three-way head styles of screws available
- ▶ Sizes available: from 1/8" Extra Short to 1/4" Long

### Perfect for:



Bathroom cabinet, curtain rod, kitchen cabinets, etc...

### Packaging:



### Product sizes & Materials

#### Plated Steel

- 1/8" XS
- 1/8" S
- 1/8" L
- 1/8" SL
- 1/8" XL
- 3/16" S
- 3/16" L
- 3/16" XL
- 1/4" S
- 1/4" L
- 1/8" SHH

### Suitable Base Materials

- ▶ Drywall 3/8 – wallboard 10 mm
- ▶ Drywall 1/2 - wallboard 13 mm
- ▶ Drywall 5/8 – wallboard 16 mm
- ▶ Hollow Block





## Hollow Wall Anchors

### Load Capacities

Material	Size	Material	Head Bolt Dia.	Drill Size	Grip Range	PULL		SHEARS		PULL		SHEARS		
						MAX	SAFE	MAX	SAFE	MAX	SAFE	MAX	SAFE	
						lbs	lbs	lbs	lbs	kg	kg	kg	kg	
Drywall 3/8 Wallboard 10 mm	1/8" XS	Plated Steel	Pan	6-32	5/16"	1/16" - 1/4"	80	40	110	55	36	18	50	25
	1/8" S	Plated Steel	Pan	6-32	5/16"	1/8" - 1/2"	80	40	110	55	36	18	50	25
	1/8" L	Plated Steel	Pan	6-32	5/16"	5/8" - 7/8"	80	40	110	55	36	18	50	25
	1/8" SL	Plated Steel	Pan	6-32	5/16"	1/8" - 1 3/16"	80	40	110	55	36	18	50	25
	1/8" XL	Plated Steel	Pan	6-32	5/16"	1 1/4" - 1 1/2"	80	40	110	55	36	18	50	25
	3/16" S	Plated Steel	Pan	6-32	5/16"	1/8" - 5/8"	90	45	130	65	41	20	59	29
	3/16" L	Plated Steel	Pan	6-32	5/16"	5/8" - 1 3/16"	90	45	130	65	41	20	59	29
	3/16" XL	Plated Steel	Pan	6-32	5/16"	1 1/4" - 1 3/4"	90	45	130	65	41	20	59	29
	1/4" S	Plated Steel	Pan	1/4"-20	7/16"	1/8" - 5/8"	95	48	150	75	43	22	68	34
	1/4" L	Plated Steel	Pan	1/4"-20	7/16"	5/8" - 1 3/16"	95	48	150	75	43	22	68	34
1/8" SHH	Plated Steel	Hex	6-32	5/16"	1/8" - 1/2"	80	40	110	55	36	18	50	25	

Material	Size	Material	Head Bolt Dia.	Drill Size	Grip Range	PULL		SHEARS		PULL		SHEARS		
						MAX	SAFE	MAX	SAFE	MAX	SAFE	MAX	SAFE	
						lbs	lbs	lbs	lbs	kg	kg	kg	kg	
Drywall 1/2 Wallboard 13 mm	1/8" XS	Plated Steel	Pan	6-32	5/16"	1/16" - 1/4"	150	75	170	85	68	34	77	39
	1/8" S	Plated Steel	Pan	6-32	5/16"	1/8" - 1/2"	150	75	170	85	68	34	77	39
	1/8" L	Plated Steel	Pan	6-32	5/16"	5/8" - 7/8"	150	75	170	85	68	34	77	39
	1/8" SL	Plated Steel	Pan	6-32	5/16"	1/8" - 1 3/16"	150	75	170	85	68	34	77	39
	1/8" XL	Plated Steel	Pan	6-32	5/16"	1 1/4" - 1 1/2"	150	75	170	85	68	34	77	39
	3/16" S	Plated Steel	Pan	6-32	5/16"	1/8" - 5/8"	175	88	180	90	79	40	82	41
	3/16" L	Plated Steel	Pan	6-32	5/16"	5/8" - 1 3/16"	175	88	180	90	79	40	82	41
	3/16" XL	Plated Steel	Pan	6-32	5/16"	1 1/4" - 1 3/4"	175	88	180	90	79	40	82	41
	1/4" S	Plated Steel	Pan	1/4"-20	7/16"	1/8" - 5/8"	200	100	200	100	91	45	91	45
	1/4" L	Plated Steel	Pan	1/4"-20	7/16"	5/8" - 1 3/16"	200	100	200	100	91	45	91	45
1/8" SHH	Plated Steel	Hex	6-32	5/16"	1/8" - 1/2"	150	75	170	85	68	34	77	39	

Material	Size	Material	Head Bolt Dia.	Drill Size	Grip Range	PULL		SHEARS		PULL		SHEARS		
						MAX	SAFE	MAX	SAFE	MAX	SAFE	MAX	SAFE	
						lbs	lbs	lbs	lbs	kg	kg	kg	kg	
Drywall 5/8 Wallboard 16 mm	1/8" XS	Plated Steel	Pan	6-32	5/16"	1/16" - 1/4"	160	80	195	98	73	36	88	44
	1/8" S	Plated Steel	Pan	6-32	5/16"	1/8" - 1/2"	160	80	195	98	73	36	88	44
	1/8" L	Plated Steel	Pan	6-32	5/16"	5/8" - 7/8"	160	80	195	98	73	36	88	44
	1/8" SL	Plated Steel	Pan	6-32	5/16"	1/8" - 1 3/16"	160	80	195	98	73	36	88	44
	1/8" XL	Plated Steel	Pan	6-32	5/16"	1 1/4" - 1 1/2"	160	80	195	98	73	36	88	44
	3/16" S	Plated Steel	Pan	6-32	5/16"	1/8" - 5/8"	190	95	210	105	86	43	95	48
	3/16" L	Plated Steel	Pan	6-32	5/16"	5/8" - 1 3/16"	190	95	210	105	86	43	95	48
	3/16" XL	Plated Steel	Pan	6-32	5/16"	1 1/4" - 1 3/4"	190	95	210	105	86	43	95	48
	1/4" S	Plated Steel	Pan	1/4"-20	7/16"	1/8" - 5/8"	220	110	220	110	100	50	100	50
	1/4" L	Plated Steel	Pan	1/4"-20	7/16"	5/8" - 1 3/16"	220	110	220	110	100	50	100	50
1/8" SHH	Plated Steel	Hex	6-32	5/16"	1/8" - 1/2"	160	80	195	98	73	37	88	44	



### Hollow Wall Anchors

#### Tools required



#### Installation instructions

1. Drill an appropriate size hole into the base material.
2. Insert the Hollow Wall Anchor into the wall. Using a screwdriver, turn the screw clockwise, until you feel resistance. This activates the wings behind the drywall.
3. Unscrew the screw from the Hollow Wall Anchor.
4. Insert the screw through the object you need to affix and screw clockwise until there is a strong resistance into the anchor.

