

INFRARED THERMOMETERS

MEASURES AND DISPLAYS SURFACE TEMPERATURE

- cULus Listed
- CLASS 2, IEC 60825-1:2014 Certification
- Optical resolution 12:1 (61-847) & 10:1 (61-827)
- LCD backlit display
- 2M drop protection (61-847); 1M drop protection (61-827)
- Minimum, Maximum, Average, Difference, Adjustable Emmisivity (61-847)



Dual Laser Targeting

61-847

Dual Laser Targeting
12:1 Infrared
Thermometer

Overmolded Industrial Grip



Single Laser Targeting

61-827

Single Laser Targeting
10:1 Infrared
Thermometer



Complies with 21 CFR 1040.10 and 1040.11 except for conformance with IEC 60825-1 Ed. 3 as described in Laser Notice No. 56 dated May 8, 2019.



Lanyard Tie-off Point



Average



Difference




Maximum



Minimum





Camera Tripod Mountable (61-847 only)



INFRARED THERMOMETERS

MEASURES AND DISPLAYS SURFACE TEMPERATURE

INFRARED THERMOMETER SELECTION GUIDE		
	61-847	61-827
FEATURES		
Listing	cULus	cULus
Certification	CLASS 2, IEC 60825-1:2014	CLASS 2, IEC 60825-1:2014
Wavelength	630nm-670nm	630nm-670nm
Output	< 1mW	< 1mW
Listing	cULs, CE	cULs, CE
Drop Protection	6.6 ft. (2m)	3.3 ft. (1m)
Optical Resolution (distance-to-spot)	12 : 1	10 : 1
Measurement Range	-26° to 932°F (-32° to 500°C)	-4° to 752°F (-20° to 400°C)
Laser Targeting	Dual	Single
Auto Scan	✓	—
Max/Min/Avg/Diff	✓	—
High/Low Alarm	✓	—
Data Hold	✓	✓
Lock-on (for continuous measurements)	✓	—
Emissivity	0.10 - 1.00 Adjustable	0.95 Fixed
Backlit Display	✓	✓
Display	LCD	LCD
Auto Power-Off	✓	✓
Selectable Celsius / Fahrenheit	✓	✓
Battery Type (included)	2 x 1.5V AAA	2 x 1.5V AAA
Low Battery Indicator	✓	✓
Response Time	250 ms	500 ms
Spectral Response	8 to 14µm	8 to 14µm
Warranty	2-Year*	2-Year*



Scan this QR code
with your smart-
phone to see more
about the
thermometers.



IDEAL INDUSTRIES, INC.

IDEAL INDUSTRIES, INC.

1800 S. Prairie Drive, Sycamore, IL 60178, USA / 815-895-5181 • 800-435-0705 in USA

International offices:

Australia • Canada • China • India • Mexico • UK

For complete sales office contact information, visit us at:

www.idealind.com