

FLEX

IT'S WHAT'S NEXT

EXCLUSIVELY* AT

LOWE'S®

To stay ahead of the trade, you need tools that do the same. Tools that aren't just part of the category but dialed in to lead it. Tools that deliver the next generation of power and work as hard as the people holding them. Whatever the next job calls for – you'll be more than ready.

THE FLEX ADVANTAGE



20% MORE POWER

Innovative design evenly distributes power to overperform in the most challenging conditions¹




25% LONGER RUNTIME

State-of-the-art THERMA-TECH™ material prevents overheating and promotes longer runtime²



50% FASTER CHARGING

Industry-leading recharge times get you back to work in as little as 30 minutes³



POWER IQ

Intelligent power management discharges at a higher output to extend performance

» DROP, DUST AND WATER RESISTANT

Engineered with a shock-resistant design and sealed electronics

* THERMA-TECH™ HEAT MANAGEMENT

Innovative cooling system minimizes heat for 25% longer runtime



» SMART CHARGE GAUGE

Indicator lights show charging levels for efficient use and easier recharging

» TWIN FAN TECHNOLOGY

Two integrated fans keep charger and battery cool to prevent overheating and provide longer life

» CHARGE IQ

Built-in intelligent processor optimizes power flow for accelerated charge time

» ADVANCED CONTROLLING SYSTEM

Automatically optimizes motor performance to deliver precise speed and power output



» WEATHER GUARD

Fully sealed electronics to protect against the elements

» SENSOR-FREE MOTOR

Software enabled processing to calculate motor partitioning for maximum performance

FLEX FOUNDERS
LIFETIME WARRANTY

FLEX FOUNDERS LIMITED LIFETIME WARRANTY NOW THROUGH DECEMBER 31, 2022

Gain exclusive access to the FLEX Founders Limited Lifetime Warranty on all FLEX 24V tools, batteries and chargers when you register within 30 days of purchase through December 31, 2022 at registermyFLEX.com.

5 YEAR WARRANTY
TOOLS • BATTERIES • CHARGERS

END-TO-END 5 YEAR WARRANTY BEGINNING 2023

Days (1,825), weeks (260.7), or five years of jobs, no matter how you measure it, a FLEX warranty runs longer. Just like our batteries and tools. Register your new products on registermyFLEX.com and get a full 5-year warranty.



*Versus national home centers for FLEX 24V. ¹FLEX 24V batteries compared to 18 volt / 20 max batteries of the same Ah. ²Comparing FLEX 24V batteries to lithium-ion batteries without THERMA-TECH™ material. ³Comparing base FLEX 160W charger to base 75W chargers with 12.0 Ah battery.

PRODUCT INNOVATIONS

All FLEX tools feature class-leading innovation and durability never before seen on the jobsite. Designed, engineered and powered to push forward, anything carrying the FLEX name guarantees it will help keep you ahead of the job when you're on the job.

FLEX offers over 60 SKUs including tools, batteries, chargers and accessories. www.FLEXPOWERTOOLS.com



1/2" 2-SPEED DRILL DRIVER WITH TURBO MODE

FX1171T-2B
Lowe's # 2590092



SPECIFICATIONS • ESPECIFICACIONES • SPÉCIFICATIONS

No-Load Speed • Velocidad sin carga • Vitesse à vide	0-550/0-2,000 RPM
TURBO Speed • Velocidad TURBO • Vitesse TURBO	0-700/0-2,500 RPM
Max. Torque • Fuerza de torsión máx. • Couple max.	1,400 in-lbs • 158 Nm
Clutch Settings • Posiciones de embrague • Paramètres de réglage de l'embrayage	22+D
Chuck Capacity • Capacidad de mandril • Capacité du mandrin	1 1/2 in • 1/2 po • 1/2 pu
Chuck Type • Tipo de mandril • Type de mandrin	Metal single-sleeve keyless ratchet with carbide teeth • Trinquete de metal sin llave de una sola manga con dientes de carburo • Cliquet sans clé en métal à un manchon avec dents en carbure
Tool Length • Longitud de la herramienta • Longueur de l'outil	7 in • 178 mm
Tool Weight (without battery) • Peso de la herramienta (sin batería) • Poids de l'outil (sans la pile)	3.7 lbs • 1.7 kg



1/4" QUICK EJECT HEX IMPACT DRIVER WITH MULTI-MODE

FX1371A-2B
Lowe's # 2590095



SPECIFICATIONS • ESPECIFICACIONES • SPÉCIFICATIONS

No-Load Speed • Velocidad sin carga • Vitesse à vide	0-1,900/2,700/3,800 RPM
Max. Impact Rate • Frecuencia de impacto máx. • Taux d'impact Max.	0-4,450 IPM
Claimed Torque • Fuerza de torsión declarada • Couple revendiqué	2,500 in-lbs • 282 Nm
Collet • Portaherramienta • Douille	Quick Eject 1/4" Hex • Quick Eject 1/4 po Hex • Quick Eject 1/4 pu Hex
Tool Length • Longitud de la herramienta • Longueur de l'outil	4.7 in • 119 mm
Tool Weight (without battery) • Peso de la herramienta (sin batería) • Poids de l'outil (sans la pile)	2.7 lbs • 1.2 kg



7 1/4" CIRCULAR SAW

FX2141-1D
Lowe's # 2590098



SPECIFICATIONS • ESPECIFICACIONES • SPÉCIFICATIONS

Saw Blade • Hoja de sierra • Lame de scie	7-1/4 in • 184 mm
No-Load Speed • Velocidad sin carga • Vitesse à vide	5,800 RPM
Bevel Capacity • Capacidad de bisel • Capacité de biseau	0-56°
Arbor • Eje portaherramienta • Arbre	5/8 in • 16 mm
Cut Capacity at 90° • Capacidad de corte a 90° • Capacité de coupe à 90°	2-5/8 in • 66 mm
Cut Capacity at 45° • Capacidad de corte a 45° • Capacité de coupe à 45°	1-7/8 in • 48 mm
Tool Weight (without battery) • Peso de la herramienta (sin batería) • Poids de l'outil (sans la pile)	9 lbs • 4 kg



RECIPROCATING SAW

FX2271-1C
Lowe's # 2590099



SPECIFICATIONS • ESPECIFICACIONES • SPÉCIFICATIONS

Stroke • Carrera • Longueur de la course	1-1/4 in • 32 mm
No-Load Speed • Velocidad sin carga • Vitesse à vide	0-3,000 SPM
Tool Weight (without battery) • Peso de la herramienta (sin batería) • Poids de l'outil (sans la pile)	7.4 lbs • 3.4 kg

*See FLEXPOWERTOOLS.COM for details.



5" VARIABLE SPEED ANGLE GRINDER WITH PADDLE SWITCH

FX3171A-1C
Lowe's # 2590105



SPECIFICATIONS • ESPECIFICACIONES • SPÉCIFICATIONS

Wheel Diameter • Diámetro del disco • Diamètre de la meule	4-1/2 - 5 in • 115 mm - 125 mm
No-Load Speed • Velocidad sin carga • Vitesse à vide	3,500 / 5,000 / 7,000 / 10,000 RPM
Switch Type • Tipo de interruptor • Type d'interrupteur	Paddle Switch, No-Lock • Interruptor de paleta, sin bloqueo • Interrupteur à palette, non verrouillable
Speed Settings • Ajustes de velocidad • Paramètres de réglage de la vitesse	4
Arbor Size • Tamaño del eje portaherramienta • Diamètre de l'arbre	5/8 in • 16 mm
Tool Weight (without battery) • Peso de la herramienta (sin batería) • Poids de l'outil (sans la pile)	4.2 lbs • 1.9 kg