KOHLER_®

Features

- Bask[®] heated surface creates spa-like relaxation with soothing warmth on your back, shoulders, and neck.
- Three heat settings allow you to customize the surface temperature.
- 120 airjets release thousands of bubbles that surround, support, and massage the body.
- Variable-speed blower lets you adjust massage intensity to 18 levels.
- Molded lumbar support offers extra comfort while bathing.
- Integral apron.
- Integral flange helps prevent water from seeping behind wall and simplifies alcove installation.
- Textured bottom surface
- Immediate and manual purge cycles remove residual water from air channels after use.
- Left-hand drain.
- Coordinates with other products in the Bancroft collection.

Material

Acrylic

Hydrotherapy

BubbleMassage

Installation

Three-wall alcove.

Recommended Accessories

K-11677 Bath Drain K-1446 Remote Installation Kit K-9497 2-1/2" Keypad Trim K-24916 Wireless Music Kit K-37380 30" Rough-in Cable Bath Drain K-37383 30" Rough-in Cable Bath Drain K-706000-D3 Frameless Sliding Bath Door K-706000-L Frameless Sliding Bath Door K-706004-D3 Frameless Sliding Bath Door K-706004-D3 Frameless Sliding Bath Door K-706004-L Frameless Sliding Bath Door K-706007-L Frameless Sliding Bath Door Bancroft®





Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 Greenguard UL 2818 - Gold

KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty KOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color Code Description


0	White
96	Biscuit
47	Almond
NY	Dune
G9	Sandbar





Bancroft® 5' BubbleMassage™ Bath K-1151-GLAW

No change in measurements if connected with drain illustrated. (K-11677)



Required Electrical Service

One dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Residual Current Device (RCD).

Blower, Heated 120 V, 15 A, 60 Hz Surface:

Technical Information

All product dimensions are nominal.

in product annoholone are noninian			
Installation:	3-Wall Alcove		
Drain location:	Left		
Basin area, bottom:	45" x 22" (1143 mm x 559 mm)		
Basin area, top:	54" x 25" (1372 mm x 635 mm)		
Weight:	106 lbs (48.1 kg)		
Minimum floor load:	49 lbs/ft² (239.2 kg/m²)		
Water depth:	15" (381 mm)		
Water capacity:	60 gal (227.1 L)		
Electrical component	Blower: 120 V, 10 A, 60 Hz		
rating:	Heated Surface: 120 V, 0.5 A, 60 Hz, 65		
	W		
Minimum flat for door:	2" (51 mm)		

Notes

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Remote blower installation kit is available for relocating the blower. Provide access for servicing the blower.

Do not relocate or alter the PVC tee or coiled flexible tubing connected to the blower. Follow the blower relocation instructions exactly.

