

# CK Plus & Premium Technical Data

## Technical Data



Certified to ANSI/UL Std. 2021  
Conforms to CAN/CSA Std. 22.2 No. 46



Model	CK 150-1 Plus	CK 150-1 Premium	CK 200-2 Plus		CK 200-2 Premium	
Item number	202031	202033	202032		202034	
Voltage	120 V	120 V	240 V or 208 V		240 V or 208 V	
Heating output stages	1	2	1		2	
Wattage	1500 W	1500 W / 750 W	2000 W	1500 W	2000 W / 1000 W	1500 W / 750 W
Max. amperage	12.5 A	12.5 A	8.3 A	7.5 A	8.3 A	7.5 A
Rated output Btu/hr	5118	5118 / 2559	6824	5118	6824	5118 / 2559
Air volume	106 CFM	106 CFM	106 CFM		106 CFM	
Recommended circuit breaker size <sup>1</sup>	15 A	15 A	15 A		15 A	
Minimum wire size (copper)	14 AWG	14 AWG	14 AWG		14 AWG	
Electrical connection	Power cord with plug, hard-wiring optional	Power cord with plug, hard-wiring optional	Junction box, rear		Junction box, rear	
User interface	Control knob	Illuminated LCD display	Control knob		Illuminated LCD display	
Timer	no	yes	no		yes	
Room size estimate	150 sq.ft.	150 sq.ft.	200 sq.ft.		200 sq.ft.	
Operating noise	48 dB(a)	48 dB(a) / 37 dB(a)	48 dB(a)		48 dB(a) / 37 dB(a)	
Heating element	nichrome wire					
Dimensions	H 18 <sup>1</sup> / <sub>2</sub> " (470 mm) x W 13 <sup>3</sup> / <sub>16</sub> " (345 mm) x D 4 <sup>15</sup> / <sub>16</sub> " (126 mm)					
Weight	11.7 lb (5.3 kg)					
Temperature range	41-86 °F (5-30 °C)					
Frost protection setting	45 °F (7 °C)					
Operating noise	49.7 dB(a)					

<sup>1</sup> This is our recommendation as the manufacturer. Check local codes for compliance if necessary.