



Main

| | |
|---------------------------|--|
| Range | Mureva |
| Range of Product | Mureva lights |
| Product name | Floodlight |
| Product or Component Type | Lamp |
| Device Application | Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas |

Complementary

| | |
|--------------------------------|-----------------------|
| Type of Installation | Outdoor |
| Operational power in W | 100 W |
| Light source | LED |
| [Ue] rated operational voltage | 120 V AC |
| Power factor | 0.9 |
| Colour rendering index | R _a =80 |
| Luminous flux | 10500 lm |
| Bulb lifespan | 50000 h |
| Colour temperature | 4000 K |
| Color | Black |
| Beam angle | 110 ° |
| Shape | Rectangular |
| Height | 11.35 in (288.4 mm) |
| Width | 8.52 in (216.4 mm) |
| Depth | 1.55 in (39.3 mm) |
| Net Weight | 4.30 lb(US) (1.95 kg) |

Environment

| | |
|---------------------------------------|----------------------------|
| Environmental characteristic | Weatherproof |
| IP Degree of Protection | IP65 |
| IK degree of protection | IK05 |
| Ambient air temperature for operation | -22...113 °F (-30...45 °C) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Environmental Disclosure

 [Product Environmental Profile](#)

Circularity Profile

 [End Of Life Information](#)
