



Main

Range	Mureva
Range of Product	Mureva lights
Product name	Floodlight
Product or Component Type	Lamp
Device Application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas




Complementary

Type of Installation	Outdoor
Operational power in W	50 W
Light source	LED
[Ue] rated operational voltage	120 V AC
Power factor	0.9
Colour rendering index	R _a =80
Luminous flux	5250 lm
Bulb lifespan	50000 h
Colour temperature	4000 K
Color	Black
Beam angle	110 °
Shape	Rectangular
Height	8.48 in (215.4 mm)
Width	6.35 in (161.4 mm)
Depth	1.22 in (31.0 mm)
Net Weight	2.25 lb(US) (1.02 kg)

Environment

Environmental characteristic	Weatherproof
IP Degree of Protection	IP65
IK degree of protection	IK05
Ambient air temperature for operation	-22...113 °F (-30...45 °C)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Environmental Disclosure

 [Product Environmental Profile](#)

Circularity Profile

 [End Of Life Information](#)
