



# PROJECT BUYING GUIDE

Terrazzo is a simple **ROLL-ON** system with these **specific products and quantities** for desired results...

#### If surface is very smooth, first prime with...







These will stop the Terrazzo coating from sliding on the floor during installation – and help ensure a uniform look and correct coverage. It also hides underlying patchiness and discoloration.

Coverage: 160 - 200 sq.ft. per 3.78l, depending on smoothness of surface and application thickness.

Otherwise, proceed directly to Terrazzo! >>

## 1) TERRAZZO



#### **Terrazzo® Granite Coating**

Coverage: 40 - 60 sq.ft. per 3.78l, per coat depending on smoothness of surface and application thickness. Apply two thin coats 24 hours apart.

## 2) SEALER







Choose this for slip-resistance on wet interior/exterior walking surfaces.

Coverage: 400 sq.ft. per 3.78I, per coat depending on smoothness of surface and application thickness.

Choose this to protect Terrazzo on garage and heavier duty surfaces.

Coverage: 400 sq.ft. per 3.78l, per coat depending on smoothness of surface and application thickness.

## TERRAZZO® PURCHASE GUIDE FOR COMMON PROJECT SIZES

	<b>Project Size</b>	<b>Primer ( x 3.78l)</b>	<b>TERRAZZO ( x 3.781)</b>	<b>SEALER ( x 3.781)</b>
Surface roughness/texture and application thickness can impact Terrazzo coverage. Apply Terrazo in two very thin coats, pressing firmly with the roller as detailed in the video.	150 Sq.Ft.	1	8	1
	200 sq.ft.	2	10	1
	250 sq.ft.	2	12	2
Purchase quantity recommendations calculated using conservative coverage rates to help ensure adequate supply	300 sq.ft.	2	15	2
	350 sq.ft.	3	18	2
	400 sq.ft.	3	20	2